



KEY FEATURES

- **DECK:**
Built to be tough and reliable. Aluminum or Steel construction. 12,000-lb structural capacity.
- **WINCH:**
Up to 12,000-lb capacity winches for maximum pulling power.
- **WHEEL LIFT:**
Low profile and versatile. 3,500-lb lift capacity. Available with manual L Arms or Autogrid.

SPECIFICATIONS

CARRIER DECK	
Capacity	12,000-lb
Deck Width	96-in, 102-in
Deck Length	20-ft, 21-ft, 22-ft
Material Type	Steel or Aluminum
WHEEL LIFT	
Lift Capacity	3,500-lb
Tow Capacity	10,000-lb
Maximum Extended Reach from End of Bed	68-in
WINCH	
Winch Capacity	10,000-lb Aluminum or Steel Deck 12,000-lb Steel Deck Only
CHASSIS	
Minimum GVWR (w/o Wheel Lift)	15,000-lb
Minimum GVWR (w/ Wheel Lift)	19,500-lb
Cab to Axle (CA) Range	120-in - 132-in (20-ft Deck) 132-in - 144-in (21-ft Deck) 144-in - 156-in (22-ft Deck)



Visit jerrdan.com for more info on warranty.

FEATURES	STANDARD	OPTIONAL
CONTROLS		
Dual Lighted Side Controls	•	
Wireless Remote (Up to 5 Functions)		•
DECK & SUBFRAME		
STEEL		
Single Sheet 3/16-in Diamond or Smooth Decking	•	
5-in Removable Tubular Steel Rails		•
5-in Polished Aluminum Blade Rails (Polished Rails standard with dual angle "Shark" Steel Decks)		•
ALUMINUM		
High Strength Extruded Aluminum Panels	•	
Patented Galvanized Steel Main Beams	•	
5-in Removeable Blade Rails (NGAR)		•
5-in Fixed Blade Rails (NGAF & NGADF "Dual Angle Deck")		•
STEEL & ALUMINUM		
96-in Deck Width	•	
102-in Deck Width		•
Center Mounted Hydraulic Valve	•	
12 Keyslots	•	
Hydraulic Pressure Gauge	•	
Hose & Wiring Track System	•	
Outboard Tilt Cylinders	•	
Rear Subframe Chain Boxes with Safety Chains	•	
Side Recovery System (SRS), (SRS-10K) Available With Combo Remote (16-in Frame Clear Space Required)		•
Galvanized Subframe & Wheel Lift		•
Greaseable Pivot Joints (Cylinders and Pivot Pins)		•
Camlocks ILO of T-Handle Manual L Arms		•
Dual Angle Deck (Aluminum Dual Angle decks are fixed rails, non removable.)		•
Hi Vis Reflective Tape Rear of Sub Frame		•
Folding 3 Step Ladder		•
Deck Approach Tip Rollers		•
LIGHTING & ELECTRICAL		
LED Lighting	•	
LED Work Lights		•
Rear Awareness Indicator Lights (RAIL)		•

FEATURES	STANDARD	OPTIONAL
TOWING ACCESSORIES		
Strap and Chain Kit: • 2- 2-in x 96-in Strap w/RTJ Hook • 2- 2-in Ratchet w/12-in Chain • 2- 5/16-in x 10-ft Chain RTJ Hooks One End and Grab Hook On The Other • 1- 5/16-in V-Chain w/RTJ Hooks Each End and Grab Hooks at Center	•	
8 Point Tie Down Kit		•
Wheel Lift Grids (Manual L Arms or Autogrid)		•
2-in or 2.5-in Reese Receiver ILO of Ball Hitch Mounting Plate (Manual L Arms)		•
Hydraulic Rear Dock Stabilizer (Various Trailer Towing Provisions Available)		•
ACCESSORIES		
Air Supply Disconnect (End of Subframe Mounted at LH Taillights)		•
SS Quarter Fenders		•
Toolbox (36-in, 48-in or 60-in)		•
Toolbox Trays		•
WINCH & WIRE ROPE		
10,000-lb Worm Gear Winch w/ 7/16-in x 56-ft EIPS Galvanized Wire Rope	•	
12,000-lb Worm Gear Winch w/ 7/16-in x 56-ft EIPS Galvanized Wire Rope		•
10,000-lb Sliding Planetary Winch w/ 7/16-in x 56-ft EIPS Galvanized Wire Rope		•
Dual Side Manual Free Spool	•	
Air Controlled Winch Free Spool		•
HEADBOARD		
Fixed Headboard Height 37-in for Ford or Ram		•
Adjustable Headboard Height 45.5-in - 65.5-in Class 6 and Above Chassis		•
Deluxe Headboard Height 36.5-in 45.5-in 50.5-in 57.5-in		•
Stationary Headboard Base Mount, Fits Standard Deck Mounted Headboards to Frame Mounted Stationary (12-in Clear Space Required)		•
Headboard Mounted Chain Racks		•
Headboard Mounted Propane Tank Holder		•
Headboard Mounted Side Grab Handles		•