



KEY FEATURES

- DECK:**
 Built to be tough and reliable. Aluminum upper deck (5,000-lb structural capacity). Aluminum and Steel construction main deck (17,000-lb structural capacity).
- WINCH:**
 8,000-lb upper deck winch. Dual 8,000-lb main deck winches.
- WHEEL LIFT:**
 Low profile and versatile. Various grid options available. 3,500-lb or 5,000-lb lift capacities.

SPECIFICATIONS	
CARRIER DECK	
Capacity (upper deck)	5,000-lb
Capacity (lower deck)	17,000-lb
Deck Width	96-in, 102-in
Upper Deck Length	14-ft
Lower Deck Length	28-ft, 30-ft
Material Type	Steel or Aluminum
WHEEL LIFT	
3,500-lb Wheel Lift	
Lift Capacity	3,500-lb
Tow Capacity	10,000-lb
Maximum Extended Reach from Tail to Bed	64-in
5,000-lb Wheel Lift	
Lift Capacity	5,000-lb
Tow Capacity	12,000-lb
Maximum Extended Reach from Tail to Bed	66-in
WINCH	
Winch Capacity	Single 8,000-lb (upper deck)
	Dual 8,000-lb (lower deck)
CHASSIS	
Minimum GVWR	33,000-lb
Cab to Axle (CA) Range	208-in - 214-in (28-ft lower deck)
	232-in - 238-in (30-ft lower deck)
Cab to Tadem (CT) Range	186-in to 192-in (28-ft lower deck)
	210-in - 216-in (30-ft lower deck)



Visit jerrdan.com for more info on warranty.

FEATURES	STANDARD	OPTIONAL
CONTROLS		
Dual Lighted Side Controls	•	
Wireless Remote (Up to 5 Functions)		•
DECK & SUBFRAME		
STEEL		
Single Sheet 3/16-in Diamond or Smooth Decking	•	
5-in Removable Tubular Steel Rails		•
5-in Polished Aluminum Blade Rails		•
ALUMINUM		
High Strength Extruded Aluminum	•	
Patented Galvanized Steel Main Beams	•	
5-in Fixed Blade Railes (NGAF)		•
STEEL & ALUMINUM		
Center Mounted Hydraulic View	•	
14 Keyslots (lower deck)	•	
4 Keyslots, 2 D-Ring Keyslots, 2 Ratchet Binders (upper deck)	•	
Hydraulic Pressure Gauge Driver Side Control Station	•	
Hose & Wiring Track System	•	
Outboard Tilt Cylinders	•	
Galvanized Subframe & Wheel Lift		•
102-in Deck Width (lower deck only)		•
LIGHTING & ELECTRICAL		
LED Lighting	•	
LED Work Lights (Rear support, top deck winch, rear lower subframe)	•	
Rear Awareness Indicator Lights (RAIL)		•

FEATURES	STANDARD	OPTIONAL
TOWING ACCESSORIES		
Wheel Lift Grids (Manual)		•
Camlocks ILO of T-Handle (Manual Grids)		•
Reese Receiver ILO of Ball Hitch Mounting Plate (Manual Grids)		•
Hydraulic Rear Dock Stabilizer (Various trailer towing provisions available) <small>*Option available when wheel lift is deleted</small>		•
ACCESSORIES		
Toolbox (36-in, 48-in or 60-in)		•
Toolbox Trays		•
WINCH & WIRE ROPE		
Dual 8,000-lb Worm Gear Winches w/ 3/8-in x 56-ft EIPS Galvanized Wire Rope (lower deck)	•	
Single 8,000-lb Worm Gear Winches w/ 3/8-in x 75-ft EIPS Galvanized Wire Rope (upper deck)	•	
Driver Side Manual Free Spool (lower deck)	•	
Air Controlled Winch Free Spool (upper deck)	•	