JERR-DAN®
An Oshkosh Corporation Business

MPL-40 INTEGRATED LIGHT DUTY WRECKER



KEY FEATURES

- **BOOM:**
  16,000-lb retracted capacity 2-stage wrecker boom.
- **UNDERLIFT:**
  Self-loading 4,000-lb lift capacity with hydraulic L-arms that feature mechanical LOCKLINK® technology.
- **BODY:**
  Modular aluminum construction, designed to provide years of service and ease of maintenance.
- **WINCHES:**
  Dual 8,000-lb worm gear winches.

RECOVERY BOOM: 2-STAGE	
Retracted Capacity @ 30°	16,000-lb
Extended Capacity @ 30°	6,000-lb
Hook Height @ 30°	109-in
Maximum Hook Height	113-in
Maximum Boom Angle	32°
REACH PAST TAILBOARD	
Reach Past Tailboard - Extended @ 0°	68-in
Reach Past Tailboard - Extended @30°	47-in
UNDERLIFT BOOM	
Retracted Rating	4,000-lb
Retracted Reach	52-in
Extended Rating	4,000-lb
Extended Reach	81-in
Positive Tilt	20°
Negative Tilt	20°
Tow Capacity	7,500-lb
WINCHES	
Dual 8,000-lb Ramsey HD-234 Worm Gear Winches*	3/8-in x 110-ft EIPS (IWRC WLL 4,300-lb) with Swivel Hook 6 x 25
SUBFRAME WITH REAR SPADES	
Read Spade Footprint	48.50-in
Ground Penetration at 34.50-in Frame Height	6-in
CHASSIS	
Minimum GVW Rating	11,000-lb
Recommended GVWR Rating	17,000-lb
Recommended Frame Height	34.50-in
Minimum Cab-to-Axle, No Tunnel, CA	60-in
Minimum Cab-to-Axle, 24-in Tunnel, CA	84-in
Maximum Cab-to-Axle, Double Tunnel, CA	108-in

Visit jerrdan.com for more info on warranty.

FULL COVERAGE 1 YEAR WARRANTY + STRUCTURAL COVERAGE 5 YEAR WARRANTY

JERR-DAN®
An Oshkosh Corporation Business

MPL-40 INTEGRATED LIGHT DUTY WRECKER

FEATURES	STANDARD	OPTIONAL
SUBFRAME		
Subframe without Rear Spade Legs	•	
Subframe with Hydraulic Rear Spade Legs & multi-position, ground compacting spade Feet*		•
CONTROLS		
Dual Side EH Controls with Control Covers	•	
Wired Underlift Remote Control	•	
Wireless Function Boom & Underlift Remote Control* (8 function)		•
Wireless Full-Function Remote Control* (14 function)		•
BODY		
Lighted Toolboxes	•	
Polished Stainless Rails		•
Aluminum Deck Dress Up Kits*		•
Inner Wheel Well Liners	•	
Black Anti-Skid Top Deck Surface	•	
24-in Aluminum Tunnel Box		•
LIGHTING & ELECTRICAL		
7-way RV/4-Way Flat Trailer Connection	•	
DOT Lighting	•	
Backup Alarm	•	
Fold Down Light Bar Mount		•
In-Cab Switch Panel		•
LED Work Lights Upper - Pylon Mounted		•
LED Lightbar		•
Backup Camera Kit		•
Steel Tubular Light Pylon		•

FEATURES	STANDARD	OPTIONAL
BOOM & WINCHES		
16,000-lb Boom with Dual Lift Cylinders	•	
Self-loading Wheel Grids w/ LOCKLINK®	•	
Underlift Level Stop Assist System	•	
Manual Loading Wheel Grids		•
Left Hand & Right Hand Remote Free Spool Handles	•	
Greasebale Joints with Grease Fittings		•
No-Lube™ Technology	•	
Dual 8,000-lb Worm Gear Winch with Tensioner Plate and Free Spool	•	
Tailboard D-rings Options		•
TOWING ACCESSORIES		
Wheel Lift Tie-Down Straps	•	
Fifth Wheel Plate*		•
Tow Sling & Mounting Brackets		•
Gooseneck Trailer Attachment*		•
Low Angle Recovery Sheave w/ Hydraulic Tilt Lockout Valve		•
Motorcycle Attachment		•
ITD Aluminum Dollies		•
Trailer Ball Attachments (available in sizes: 1-7/8-in, 2-in, 2-5/16-in)*		•



JERRDAN.COM
(800) 926-9666

Part No: 202001
R0126_01