JERR-DAN®
An Oshkosh Corporation Business

JD35 INTEGRATED HEAVY DUTY WRECKER



KEY FEATURES

- **BOOM:**
  70,000-lb retracted capacity 2-stage wrecker boom.
- **UNDERLIFT:**
  350 series underlift options – 350 3-stage 35,000-lb retracted capacity with 128-in of reach, 350X 3-stage 35,000-lb retracted capacity with 147-in of reach, and low profile 350XLP 3-stage 35,000-lb retracted capacity with 143-in of reach.
- **BODY:**
  Built with a polypropylene copolymer material that is high-impact resistant and corrosion-free.

2-STAGE RECOVERY BOOM			
Rated Capactity @ 30° Retracted	70,000-lb		
Rated Capactity @ 30° Extended	22,000-lb		
REACH PAST TAILBOARD			
Extended @ 0°	132-in		
Extended @ 30°	87-in		
OPERATING RANGE			
Maximum Boom Angle	39°		
Maximum Hook Height	225-in		
WINCHES & WIRE ROPE			
Rated Capacity - Dual Boom Mounted Planetary Winches	35,000-lb each		
Rated Working Load Limit - 5/8-in x 200-ft EIPS Galvanized	11,700 -lb		
Rated Working Load Limit - 5/8-in x 250-ft EIPS Galvanized	11,700-lb		
Rated Working Load Limit- 3/4-in x 200-ft EIPS Galvanized	16,800-lb		
UNDERLIFT			
Centerline of Tandem Axle to Tailboard	66-in		
MODEL	350	350X	350XLP
Rated Capacity - Retracated	35,000-lb	35,000-lb	35,000-lb
Rated Capacity- Extended	16,000-lb	16,000-lb	16,000-lb
Reach Past Tailboard- Retracted with Forks at Ground Level	63-in	69-in	71-in
Reach Pasat Tailboard- Extended with Forks at Ground Level	128-in	147-in	143-in
Positive Tilt	20°	20°	20°
Negative Tilt	10°	10°	10°
Tow Capacity	80,000-lb	80,000-lb	80,000-lb
CHASSIS RECOMMENDATION			
Minimum GVW Rating	54,000-lb		
Minimum RBM Per Rail	3,250,000-in-lb		
Minimum Front Axle Weight Rating	14,600-lb		
Minimum Rear Axle Weight Rating	40,000-lb		
Ride Height	12-in		
Frame Height Maximum	45-in		
Minimum After Frame Length	70-in		

FULL COVERAGE 1 YEAR WARRANTY + STRUCTURAL COVERAGE 5 YEAR WARRANTY

Visit jerrdan.com for more info on warranty.

JERR-DAN®
An Oshkosh Corporation Business

JD35 INTEGRATED HEAVY DUTY WRECKER

FEATURES	STANDARD	OPTIONAL
CONTROLS		
Passenger Side Manual Controls with Passenger Side Hydraulic Pressure Gauges	•	
Driver Side Electric over Hydraulic Paddle Controls	•	
Driver Side Hydraulic Gauge		•
Color Coded Winch Control Handles	•	
Color Coded Winch Sheave Guides and Hooks		•
Hydraulic Tank with Fluid Level Sight Gauge & Return Filter with Life Indicator	•	
Non-Proportional Underlift Remote	•	
Non-Proportional Boom/Winch/Underlift Remote		•
Proportional Boom/Winch Remote		•
Touchlink In-Cab Underlift Controls		•
BODY & TUNNEL		
Structural Polypropylene Copolymer Body	•	
Anti-Skid Diamond Plate Walking Surface	•	
Painted Roll-Up Doors and Door Frames	•	
Forward Facing Diamond Plate on Tunnel Box		•
Storage Solutions for Tools and Equipment (Bronze, Silver & Gold)		•
LIGHTING & ELECTRICAL		
Integrated Electronic Distribution System	•	
Touchlink Control System for Lighting and Winches with Integrated E-Stop	•	
Interior Tool Box Lighting (LED)	•	
Clear Body Marker Lights (LED)	•	
Lighted Steps & Grab Handle (LED)	•	
Upper Hook-Up Lights (LED)	•	
Lower Hook-Up Lights (LED)	•	
Upper Work Lights-Pylon Mounted (LED)	•	
Underlift Hook-Up Light (LED)	•	
Hood Mounted Flashers		•
Grille Mounted Flashers		•
Body Mounted Flashers		•
Main Light Bar		•
Wing Light Bars		•

FEATURES	STANDARD	OPTIONAL
BOOM, UNDERLIFT & WINCHES		
2-Stage Recovery Boom	•	
Boom Mounted D-Rings	•	
Hydraulic Rear Spades with Ground Compacting Spade Foot	•	
350XLP- Low Profile, 143-in Reach	•	
350 Underlift, 128-in Reach		•
350X Underlift, 147-in Reach		•
5-in Crossbar Pivot Pin	•	
Integrated Safety Chain Storage	•	
Dual Planetary 35,000-lb 2-Speed Winches	•	
Air Free Spool with Adjustable Rope Tensioner	•	
Winch Camera with Control Station Monitors		•
TOWING ACCESSORIES		
7-Way Trailer Plug	•	
Recessed Glad Hands	•	
Service Air Quick Connect	•	
9 Sets of Frame Forks with Fork Receivers (Included with Every Underlift Model)	•	
Chain End Caps	•	
Backup Camera		•
Rear Facing Underlift Camera		•
High Rise Fork Receivers		•
25K Bus Arms/Tire Lifts		•
5th Wheel Attachment		•
Pintle Hitch Attachment		•
Rigging Kits (Sling Kits, HD Chain Kits, Snatch Block Kits, & Shackle Kits)		•
Tunnel Box Counterweight Options		•
ACCESSORIES		
Side Recovery System (35,000-lb Winch)		•
Side Stabilization System (SS-70-No winch)		•
Stainless Steel Rubrail Dress Up Kit	•	
Stainless Steel Pylon Dress Up Kit	•	