JERR-DAN®
An Oshkosh Corporation Business

MPL-NGS INTEGRATED LIGHT DUTY WRECKER



KEY FEATURES

- **UNDERLIFT:**
  Self-Loading 4,000-lb lift capacity with hydraulic L-arms that feature mechanical LOCKLINK® technology.
- **BODY:**
  Steel welded body with diamond plate top decking.
- **WINCH:**
  8,000-lb single worm gear winch.

UNDERLIFT BOOM	
Retracted Rating	4,000-lb
Retracted Reach	49-in
Extended Rating	4,000-lb
Extended Reach	78-in
Positive Tilt	15°
Negative Tilt	7°
Tow Capacity	7,500-lb
WINCH	
Winch Capacity	8,000-lb
Winch Options	Single
Wire Rope (EIPS Galvanized)	3/8-in x 75-ft or 3/8-in x 110-ft
CHASSIS	
Minimum GVW Rating	11,000-lb
Recommended GVWR Rating	17,000-lb
Recommended Frame Height	34.50-in
Minimum Cab-to-Axle, No Tunnel, CA	60-in
Minimum Cab-to-Axle, 24 in. Tunnel, CA	84-in

Visit jerrdan.com for more info on warranty.

FULL COVERAGE 1 YEAR WARRANTY + STRUCTURAL COVERAGE 5 YEAR WARRANTY

JERR-DAN®
An Oshkosh Corporation Business

MPL-NGS INTEGRATED LIGHT DUTY WRECKER

FEATURES	STANDARD	OPTIONAL
CONTROLS		
Wired Remote Control	•	
Wireless Remote Control		•
BODY		
Lighted Toolboxes	•	
Polished Stainless Rails		•
Aluminum Deck Dress Up Kits*		•
24-in Aluminum Tunnel Box		•
LIGHTING & ELECTRICAL		
7-way RV/4-Way Flat Trailer Connection	•	
DOT Lighting	•	
Backup Alarm	•	
Fold Down Light Bar Mount		•
In-Cab Switch Panel		•
LED Work Lights Upper - Pylon Mounted		•
LED Lightbar		•
Backup Camera Kit		•
Steel Tubular Light Pylon	•	

FEATURES	STANDARD	OPTIONAL
WINCH		
Single 8,000-lb Worm Gear Winch with Wire Tensioner Plate and Free Spool		•
Remote Free Spool Handles	•	
Tailboard D-Rings Options		•
UNDERLIFT		
Underlift Level Stop Assist System	•	
Self-Loading Wheel Grids w/ LOCKLINK® Technology	•	
Manual loading Wheel Grids		•
Greaseable Joints w/ Grease Fittings		•
No-Lube™ Technology	•	
**Available through parts only*		

JERRDAN.COM
(800) 926-9666