

UTILITY HOSES SUPPLIES



ONE PURCHASE ORDER, MULTIPLE HOSE SOLUTIONS.

Simplify purchasing, reduce customer downtime, and keep inventory on hand with a reliable source for the most commonly used hose products.

JACK HAMMER HOSES

- For use with mobile air compressors to 300-lb working pressure
- Black, oil mist resistant rubber tube, two braid equivalent of polyester spiral reinforcement
- Abrasion and sunlight resistant EPDM rubber cover



DESCRIPTION	INDIVIDUAL	PALLET	
	PART NUMBER	PART NUMBER	QTY
3/4-in x 50-ft Goodyear Jack Hammer Hose	70400860	70400861	50
3/4-in x 50-ft Standard Duty Jack Hammer Hose	70400862	70400863	35

STANDARD GRADE CAMLOCK DISCHARGE HOSES

Application:

- Economy grade, PVC hose for portable pump and irrigation use
- Layflat hose for easy coiling and handling

Temperature Range: 23°F to 131°F (-5°C to 55°C)

Tube: PVC

Reinforcement: Polyester yarn

Cover: Blue or Gray PVC



DESCRIPTION	PART NUMBER
2-in x 50-ft Discharge Hose, Blue Service Level, MxF Camlock	70400865
3-in x 50-ft Discharge Hose, Blue Service Level, MxF Camlock	70400864
4-in x 50-ft Discharge Hose, Blue Service Level, MxF Camlock	70400867

HD DISCHARGE CAMLOCK HOSES

Application:

- More rugged than blue and gray PVC layflat discharge hoses
- Designed for use where higher working pressures are required
- Layflat hose for easy coiling and handling

Temperature Range: -5°F to 170°F (-21°C to 77°C)

Tube and Cover: 3-ply polyester yarns. both tube and cover are extruded simultaneously to obtain maximum bonding



DESCRIPTION	PART NUMBER
3-in x 50-ft HD Discharge Hose, Red Service Level, MxF Camlock	70400866

ORDER TODAY | onlineexpress.jlg.com | AllFleet@jlg.com

PART NO. 3131136 | R0225_02



JLG INDUSTRIES, INC.
Toll-free US 877-JLG-LIFT
JLG.com

An Oshkosh Corporation Business