JERR-DAN®
An Oshkosh Corporation Business

10 TON XLP WOOD INDUSTRIAL CARRIER MEDIUM DUTY CARRIER



KEY FEATURES

- **DECK:**
  Built to be tough and reliable with apitong wood construction. 20,000-lb structural capacity.
- **WINCH:**
  Up to 12,000-lb capacity Worm Gear Winch for maximum pulling power.
- **REAR TOW:**
  Options from rear dock stabilizer with extendable pintle hitch or wheel lift with hitch.

CARRIER DECK	
Capacity	20,000-lb
Deck Width	102-in
Deck Length	24-ft, 26-ft, 28-ft
Material Type	Apitong Wood
TOW & STABILIZER OPTIONS	
STATIONARY TOW	
Pintle Hitch Plate	4,000-lb Tongue Weight 15,000-lb Tow
2.5" Reese Receiver	10,000-lb
REAR DOCK STABILIZER	
Lift Capacity	3,500-lb
Tow Capacity	20,000-lb
5,000-LB WHEEL LIFT	
Lift Capacity	5,000-lb
Tow Capacity	12,000-lb
Maximum Extended Reach from Tail to Bed	67-in
WINCH	
Winch Capacity	Single 12,000-lb
CHASSIS	
Minimum GVWR (w/ Wheel Lift)	33,000-lb
Cab to Axle (CA) Range	156-in - 168-in (24-ft Deck) 180-in - 192-in (26-ft Deck) 204-in - 214-in (28-ft Deck)
Cab to Tandem (CT) Range	134-in - 146-in (24-ft Deck) 158-in - 170-in (26-ft Deck) 182-in - 196-in (28-ft Deck)
Minimum After Frame (CA)	38-in
Minimum After Frame (CT)	60-in

FULL COVERAGE 1 YEAR WARRANTY + XLP HYDRAULIC COVERAGE 3 YEAR WARRANTY + STRUCTURAL COVERAGE 5 YEAR WARRANTY

Visit jerrdan.com for more info on warranty.

JERR-DAN®
An Oshkosh Corporation Business

10 TON XLP WOOD INDUSTRIAL CARRIER MEDIUM DUTY CARRIER

FEATURES	STANDARD	OPTIONAL
CONTROLS		
Dual Lighted Side Controls	•	
Wireless Remote (Up to 5 Functions)		•
DECK & SUBFRAME		
102-in Deck Width	•	
Center Mounted Hydraulic Valve	•	
Outside Keyslots: 24' Deck: 26 26' Deck: 28 28' Deck: 30	•	
Inside Keyslots: 24' Deck: 22 26' Deck: 24 28' Deck: 26	•	
Hydraulic Pressure Gauge	•	
Hose & Wiring Track System	•	
Outboard Tilt Cylinders	•	
Patented No-Lube Technology	•	
Hi Vis Reflective Tape Rear of Sub Frame		•
Greaseable Piviot Joints (Cylinders and Pivot Pins)		•
3 Step Folding ladder (Driver, Passenger, or Both)		•
Yellow Anti-Slip on Approach Tip		•
Yellow Anti-Slip on Rub Rails		•
Side Recovery System (SRS) (SRS-10K) Available with Combo Remote (16-in of Frame Clear Space Required)		•
Galvanized Subframe & Wheel Lift		•
LIGHTING & ELECTRICAL		
LED Lighting	•	
LED Work Lights (Rear support, Deck winch, Rear lower subframe)		•
Rear Awareness Indicator Lights (RAIL)		•
ACCESSORIES		
Air Supply Disconnect (End of Subframe Mounted at LH Taillights)		•
Stainless Steel Quarter Fenders		•
Toolbox (36-in, 48-in or 60-in)		•
Toolbox Trays		•
Traffic Cone Storage		•

FEATURES	STANDARD	OPTIONAL
TOWING ACCESSORIES		
Strap and Chain Kit: · 2- 2-in x 96-in Strap w/RTJ Hook · 2- 2-in Ratchet w/12-in Chain · 2- 5/16-in x 10-ft Chain, RTJ Hooks One End and Grab Hook on the Other · 1- 5/16-in V-Chain w/RTJ Hooks Each End and Grab Hooks at Center		•
8 Point Tie Down Kit		•
Trailer Glad Hands & 7 Way Connector with Mounting Bracket		•
Wheel Lift Grids (Manual L Arms)		•
Camlocks ILO of T-Handle Manual L Arms		•
Reese Receiver ILO of Ball Hitch Mounting Plate (Manual Grids) 2-in or 2.5-in Reese Available		•
WINCH & WIRE ROPE		
12,000-lb Worm Gear w/ 7/16-in x 56-ft EIPS Galvanized Wire Rope	•	
HEADBOARD		
Adjustable Headboard Height 45.5-in - 65.5-in Class 6 and Above Chassis		•
Deluxe Headboard Height 45.5-in, 50.5-in, 57.5-in		•
Frame Mounted Stationary Base Mount with Adjustable Headboard		•
Headboard Mounted Chain Racks		•
Headboard Mounted Propane Tank Holders and Chain Racks		•
Headboard Mounted Side Grab Handles		•

JERRDAN.COM
(800) 926-9666